

KRACKFIX

TECHNICAL DATA SHEET



Polymer-Modified Cement-Based White Crack Fill Powder

Description

Fixup® KRACKFIX is a high-performance, polymer-modified white cement-based crack filler powder designed for interior and exterior applications. This easy-to-use, white powder is specially formulated to repair cracks up to 3 mm and minor surface defects in plaster, concrete, and masonry walls, providing a smooth, durable, and paintable finish.

Where to Use

- Filling cracks in walls, ceilings, and concrete surfaces.
- Sealing minor surface defects before painting or plastering.
- Repairing shrinkage cracks in cement-based substrates.
- Suitable for interior and exterior applications.

Benefits & Features

- Bonds well with concrete, plaster, and masonry.
- Prevents further cracking and shrinkage.
- Protects against moisture ingress.
- Can be applied with a putty knife or trowel.
- Quick-drying for faster project completion.

Technical Information

Property	Value/Range
Appearance	White Powder
Mixed Density	1.60 ± 0.05 kg/ litre
Pot life @ 30°C	30-45 minutes
Crack filling size	Up to 3 mm
Sag Resistant	Non-sag
Water Absorption	<2%
Paint ability	Excellent
Packing	1 kg, 5 kg

How to Apply

- Ensure the surface is clean, dry, and free from dust, grease, and loose materials. Pre-wet the area lightly before application.
- Gradually add the powder to water and mix thoroughly until a smooth, lump-free paste is formed. Avoid excessive water.
- Apply the paste using a putty knife or trowel, pressing it firmly into the cracks.
- Smooth out the surface with a damp sponge or trowel. Allow to dry completely before painting or further finishing.
- No water curing is required, but avoid exposure to direct water for 24 hours.
- Clean tools with water immediately after use.

KRACKFIX

TECHNICAL DATA SHEET



Storage & Shelf Life

- Store in a cool, dry place, away from moisture and direct sunlight.
- Shelf life: 12 months in unopened packaging.

Safety & Precautions

- Use protective gloves and goggles during handling.
- In case of contact with eyes or skin, rinse immediately with plenty of water.
- Do not ingest; seek medical attention if swallowed.

Disclaimer

While the technical details & recommendations contained in this document and the related details given by the representatives of the company correspond to the best of our knowledge & experience, all the above information must in any case be considered as merely indicative and subject to confirmation. Users are recommended to conduct a product suitability test before it is used at full scale. In any case, the consumer alone is entirely liable for any consequences resulting from using the product. For the most up-to-date TDS, please visit our website at www.fixup.co.in. Our company policy is one of ongoing R&D; therefore, we reserve the right to update this information without prior notice at any time. As the correct identification of the problems, the quality of other materials used, on-site environmental conditions and the workmanship on-site are factors beyond our control, there is no express or implied guarantee/warranty as to the results achieved. The company assumes no liability or consequential damage arising from the use of our products for unsatisfactory results. Site visits are not a supervisory responsibility wherever provided. Suggestions made either verbally or in writing by the company may be followed, modified or rejected by the owner, engineer or contractor, since they are solely responsible for carrying out procedures appropriate to a specific application.