

TECHNICAL DATA SHEET

ECOFIX 232



Two Part Polyurethane Base Tile & Stone Adhesive



Description

Fixup® EcoFix 232 is a two-part polyurethane tile adhesive, a high-performance solution for bonding ceramic, vitrified, natural stone, and speciality tiles on challenging substrates—including metal, plywood, drywall, and even heated subfloors.

Engineered for reliability in both interiors and exteriors, this adhesive delivers exceptional flexibility, waterproofing, and chemical resistance.

Features and Benefits

- Superior Bond Strength
- Exceptional Flexibility
- Waterproof & Chemical Resistant
- Broad Substrate Compatibility

Instructions for Use

- Ensure substrates are dry, clean, and free from grease, oil, or dust.
- Add full quantity of Part B (Hardener) to Part A (Resin); mix mechanically for 3–5 minutes until uniform.
- Apply using a notched trowel, ensuring recommended bed thickness.
- Allow open time as specified; place tiles within this window, adjusting as needed.
- Clean tools with suitable solvents before adhesive cures.

Technical Data

Property	Value/Range
Appearance	Off-white to white paste (Mixed)
Mixed Density	1610-1710 kg/m ³
Open Time	>60 min.
Pot Life	~40 - 60 min
Cure Time	~24 hours
Application Temperature	10 °C - 40 °C
Shelf Life	12 months
Coverage	4-5 sq. ft./ kg 1.5 mm bed thickness (3X3 mm notch trowel)

Safety & Precautions

- Store in cool & dry place.
- Avoid contact with skin and eyes. In case of contact, rinse thoroughly with water and seek medical advice if necessary.
- Ensure good ventilation when using the product.
- Use gloves and eye protection when handling the product.

Disclaimer-Fixup products and recommendations are provided in good faith based on our experience, but they should be treated as indicative only. Users must confirm product suitability for their specific application, as site conditions and workmanship are beyond our control. Final responsibility for results rests solely with the user. For the latest TDS, visit www.fixup.co.in.