

TECHNICAL DATA SHEET

TFIX-F3(GREY) / TFIX-F4(WHITE)



Highly Polymerized, Grey / White Glass Mosaic and Stone Adhesive



Description

Fixup® TFIX-F3(GREY) /TFIX-F4(WHITE) is a single component, high performance tile adhesive consists of distinguished blend of cement, well graded minerals and high content of modified polymers that forms when mixed with water an outstanding tile adhesive that capable for fixing all types of large ceramic tiles and natural stone on all common construction substrates internally or externally.

Features and Benefits

- Shrinkage and crack resistance
- Ultimate stability & dual bonding strength
- No vertical slip
- Extended open time
- Shock & impact resistance
- Superior workability

Instructions for Use

- Clean and prepare the substrate, ensuring it is free from dust, dirt, and other contaminants.
- Mix the adhesive with water at a ratio of 1:4 by weight.
- Mix thoroughly until a smooth, lump-free consistency is achieved.
- Apply the adhesive to the substrate using a notched trowel, ensuring full coverage.
- Lay the tiles into the adhesive, pressing firmly and ensuring they are level.
- Allow the adhesive to dry for at least 24 hours before allowing light foot traffic.
- Grout the tiles using a suitable grout after the adhesive has fully cured.

Technical Data

Appearance	Grey/White Powdered Mixture
Adjustment Time	~20 ± 5 minutes
Open Time	~30 ± 5 minutes
Pot Life	~60 ± 30 minutes
Shear Adhesion	1.5 N/mm ² @ 28 days (Dry condition)
Tensile Adhesion	1.5 N/mm ² @ 28 days (Dry condition)
Time to Traffic	~24 Hours
Water Demand	~25 ± 5% by weight
Shelf Life	12 months from the date of manufacturing
Coverage	~50 - 60 square feet /25 kg bag (For, 3 mm bed thickness)

Safety & Precautions

- Store in cool & dry place.
- Avoid contact with skin and eyes. In case of contact, rinse thoroughly with water and seek medical advice if necessary.
- Ensure good ventilation when using the product.
- Use gloves and eye protection when handling the product.