

## Polymer modified cement based grout for tiles joints/groove filling



### Description

Fixup<sup>®</sup> PG 101 is a versatile and durable solution for filling joints and gaps. It improves the adhesion, flexibility, and resistance to cracking and shrinkage of the grout.

### Features and Benefits

- Good bond strength and adhesion
- Water resistant and low permeability
- Suitable for use in tropical conditions
- Available in various colours
- UV, mould and fungus resistant
- Easy mixing and application (add only water)
- For joint widths of 1–6 mm

### Instructions for Use

- Ensure that the surface to be grouted is clean and free from dust, oil, and other contaminants.
- Mix the polymer modified cement grout with water according to the manufacturer's instructions
- Apply the grout using a grouting pump or a trowel, ensuring that all voids are filled.
- Compact the grout to ensure full penetration and to eliminate air pockets.
- Allow the grout to cure for the recommended time, keeping it moist and protected from excessive heat and cold.
- After the grout has cured, clean the surface and remove any excess grout using a grout sponge or a damp cloth.

### Technical Data

Property	Value/Range
Appearance	Fine Powder
Mixed Density	1.60 ± 0.05 kg/ litre
Pot life @ 30°C	60 minutes
Joint Width	Up to 3 mm
Sag Resistant	Non-sag
Application Temperature	From +10° C to +35° C
Light Foot Traffic	24 hours
Packing	1 kg, 5 kg & 40 kg

### Precautions

- Store in a cool, dry area away from moisture
- In case of contact with skin and eyes, rinse thoroughly with water and seek medical advice if necessary.
- Use gloves and eye protection when handling the product.