

TECHNICAL DATA SHEET

PLASTOFIX 100



Integral waterproofing compound for plaster



Description

Fixup® PLASTOFIX 100 is a high-performance plaster admixture designed to enhance workability and durability in cement-based plaster applications. It improves cohesion, reduces plastic shrinkage and increases the ease of application, ensuring a smooth, crack-resistant finish.

Features and Benefits

- Enhances plaster consistency and application ease.
- Helps achieve the desired consistency with less water.
- Reduces the risk of cracks due to plastic shrinkage.
- Improves long-term strength and resistance to weathering.

Instructions for Use

- Add the recommended dosage directly into the mixing water before incorporating into the plaster mix.
- Ensure uniform dispersion by mixing thoroughly for 3-5 minutes.
- Apply the plaster mix using traditional tools or spray application methods.
- Follow standard curing practices to achieve optimum strength and durability.

Technical Data

Appearance	Brown liquid
Ph	7.0 – 9.0
Specific Gravity @25 °C	1.0 – 1.1
Solubility	Soluble in water
Chloride Content	Nil
Compatibility	Compatible with all types of Portland cement
Recommended Dosage	80 - 100 gm per 50kg cement bag
Packing	5 kg, 20 kg

Safety & Precautions

- Store in cool & dry place.
- Avoid contact with skin and eyes. In case of contact, rinse thoroughly with water and seek medical advice if necessary.
- Ensure good ventilation when using the product.
- Use gloves and eye protection when handling the product.

Disclaimer-Fixup products and recommendations are provided in good faith based on our experience, but they should be treated as indicative only. Users must confirm product suitability for their specific application, as site conditions and workmanship are beyond our control. Final responsibility for results rests solely with the user. For the latest TDS, visit www.fixup.co.in.