

Free flow, high strength, non-shrink cementitious precision grout



Description

Fixup® FLOWFIX GP is free flow non-shrink cementitious grout which is one-component, ready-to-mix, and free-flowing. It contains a unique shrinkage compensating mechanism to ensure that it maintains its volume once set. It is commonly used for grouting applications where high fluidity, strength, and durability are essential.

Features and Benefits

- Enhanced Structural Integrity
- Precise Placement
- Time and Labour Savings
- Long-Term Performance
- Minimized Maintenance
- Versatile Applications

Instructions for Use

- Clean and prepare the substrate; ensure it is dry, sound, and free from dust, oil, or grease.
- Add grout powder slowly to mixing while mixing to obtain a smooth, lump-free consistency.
- Pour the mixed grout into the area, ensuring complete filling of gaps and voids.
- Compact the grout using a trowel to remove air pockets and ensure proper bonding.
- Place bolts or equipment while the grout is still workable, if required.
- Level and finish the surface with a trowel as needed.
- Protect the grout during curing and clean tools immediately after use.

Technical Data

Appearance	Grey Powdered Mixture
Wet Density	2200 ± 100 Kg/m ³
Consistency	Water / Powder Ratio
Pourable	0.16
Flow able	0.17
Free flow	0.18
Flow	190-220 mm
Tensile strength	>3.5N/mm ² @ 28 days
Compressive Strength	>65 N/mm ² @ 28 days
Flexural strength	>10 N/mm ² @ 28 days
Packing size	25 kg
Shelf Life	12 months from the date of manufacturing

Precautions

- Store in a cool, dry area away from moisture
- In case of contact with skin and eyes, rinse thoroughly with water and seek medical advice if necessary.
- Use gloves and eye protection when handling the product.