

GA-102^(CEMENT GROUT ACTIVATOR)

TECHNICAL DATA SHEET



A liquid admixture designed to enhance the performance of cementitious grouts.

Description

Fixup® GA-102 is a chemical additive designed to enhance the performance of cement-based grouts. It is formulated to accelerate the setting and curing process of cementitious grouts, improving their strength, durability, and bonding properties.

Where to Use

Grouting applications in concrete and masonry construction, including:

- Filling cracks and voids
- Anchoring bolts and dowels
- Grouting around precast concrete panels

Benefits & Features

- Improved workability of grout.
- Increased early and ultimate strength.
- Enhanced bond strength to substrate.
- Improved water resistance and permeability.
- Reduced shrinkage.

Technical Information

Property	Value/Range
Appearance	Liquid
Colour	Milky White
pH	8.0 – 10.0
Specific Gravity @25 °C	1.02 – 1.04
Solubility	Soluble in water
Recommended Dosage	200–250 ml per 1 kg cement grout
Packing	250ML & 1L

How to Apply

- Ensure the substrate surface is clean, dry, and free from any contaminants.
- Mix Fixup® GA-102 with the required amount of water according to the recommended dosage.
- Add the mixture to the cement-based grout powder and mix thoroughly until a uniform consistency is achieved.
- Apply the activated grout mixture onto the prepared substrate using appropriate tools.

Precautions and limitations

- Do not increase the dosage of Fixup® GA-102 than the recommendation.

Health & Safety

- Wear appropriate personal protective equipment (PPE) such as gloves, safety glasses, and a respirator if necessary.
- Avoid contact with skin, eyes, and clothing. If contact occurs, immediately flush the affected area with water and seek medical attention if necessary.
- Keep out of reach of children. Limited to professional use only.

GA-102^(CEMENT GROUT ACTIVATOR)

TECHNICAL DATA SHEET



Disclaimer

While the technical details & recommendations contained in this document and the related details given by the representatives of the company correspond to the best of our knowledge & experience, all the above information must in any case be considered as merely indicative and subject to confirmation. Users are recommended to conduct a product suitability test before it is used at full scale. In any case, the consumer alone is entirely liable for any consequences resulting from using the product. For the most up-to-date TDS, please visit our website at www.fixup.co.in. Our company policy is one of ongoing R&D; therefore, we reserve the right to update this information without prior notice at any time. As the correct identification of the problems, the quality of other materials used, on-site environmental conditions and the workmanship on-site are factors beyond our control, there is no express or implied guarantee/warranty as to the results achieved. The company assumes no liability or consequential damage arising from the use of our products for unsatisfactory results. Site visits are not a supervisory responsibility wherever provided. Suggestions made either verbally or in writing by the company may be followed, modified or rejected by the owner, engineer or contractor, since they are solely responsible for carrying out procedures appropriate to a specific application.